

Extinguisher drying unit

DRY series

TO QUICKLY REMOVE THE MOISTURE GENERATED INSIDE EXTINGUISHERS/CYLINDERS BY HYDRAULIC TESTING



ADVANTAGES

Reduced dimensions and low power consumption make the DRY2 unit easy to use in the shop or on board a mobile workshop. The DRY6 unit ensures high productivitity by drying several extinguishers simultaneously.

COMPONENTS AND DEVICES

- > Lateral blower
- > Fast warming resistance
- > Insulated main manifold
- > Timer for work time setting
- > Main switchboard with 24V. controls

STANDARD EQUIPMENT

> User manual

AVAILABLE MODELS

- > DRY2 single-phase
- > DRY6 three-phase



Extinguisher drying unit, DRY series





OPTIONALS

DESCRIPTION	MODEL	CODE
Wheeled extinguisher accessory	DRY2WE	AZEE002
Wheeled extinguisher accessory	DRY6WE	AZEE006

TECHNICAL SPECIFICATIONS

MODEL	DRY2	DRY6/4	DRY6/10
CATALOG ITEM	MZEE002	MZEE001	MZEE003
EXTINGUISHER PLACES	2	6	6
NUMBER OF EXTINGUISHERS PER HOUR (6kg CAPACITY)	12	36	48
WHEELED EXTINGUISHERS PLACES WITH WE ACCESSORY	1	2	3
NUMBER OF EXTINGUISHERS PER HOUR WITH WE ACCESSORY	2	4	8
VOLTAGE/FREQUENCY (VAC/Hz)	230/50	400/50	400/50
BLOWING POWER (kW)	0.37	1.1	1.5
RESISTANCE POWER (kW)	0.77	4	10
DIMENSIONS (WxLxH) (mm)	870x370x685	2000x500x700	2000x500x700
WEIGHT (Kg)	30	70	75

Models for different voltages and frequencies are available on request

VANZETTI EQUIPMENT SRL

Via Avv. Giovanni Agnelli, 10 12033 Moretta (CN) ITALY

Tel. (+39) 0172 915811 Fax (+39) 0172 915822

info@vanzettiequipment.com

www.vanzettiequipment.com



