

Manual pneumatic vice for **CNG** cylinders

AIR-M series



TECHNICAL DEVICES

- Big diameter pneumatic cylinder
- Rubber covered jaws
- Two-hand operated closing device (EC)
- Varnished steel support base set to be fixed to the wall or to the floor (AIR5-M model)
- Adjustable locking to the cylinder different Ø
- Mobile and removable base with "fast-lock" device (AIR5-M)
- Use and maintenance manual

OPERATIONS

AIR-M pneumatic vices allow to safely and efficiently lock the cylinders. With them, you can easily achieve the valving / devalving operations with the torque wrench. These units have been designed for heavy-duty operations, wherever you need to reach high tightening torque on the cylinder valves.

ADVANTAGES

- the coupling torque works in accordance with what required by the valve manufacturers.
- Reduced physical effort

FEATURES

The AIR-M pneumatic vice for cylinders is made of varnished steel and is available in two versions. The AIR4-M is to be fixed to the wall or to a specific support. The AIR5-M is already equipped with a self-standing support base.

AVAILABLE MODELS

MODEL	AIR5-M	AIR4-M
Catalogue code	MZAP061	MZAP050
Min locking diameter (mm)	170	170
Max locking diameter (mm)	410	410
Max working pressure (bar)	10	10
Dimensions (WxLxH) mm	1000x700x1300	1000x400x1300
Weight (kg)	140	52

PER MAGGIORI INFORMAZIONI
FOR FURTHER INFORMATION
POUR ULTERIEURES INFORMATIONS

VANZETTI EQUIPMENT S.r.l. Unipersonale

Via Avv. Giovanni Agnelli 10
12033 MORETTA (CN) ITALY
Tel: +39 0172 915811 – Fax: +39 0172 915822

info@vanzettiequipment.com
www.vanzettiequipment.com



BULLETIN N°VE/AIR-M-E